

APL限位开关-2,3,4,5N系列

Valve Position Monitor APL-2,3,4,5N Series

APL-2N 系列



- ◆ 防护等级: IP67/NEMA 4& 4X (标准) IP68 (选项)
- ◆ 外壳设计坚固紧凑
- ◆ 开关位置可由指示器清楚辨识
- ◆ 双线接口: 双1/2NPT管接口 (标准) M 20, PG 13.5, PF1/2" (选项)
- ◆ 接线端子: 8点 0.08-2.5mm²
- ◆ 防脱螺栓
- ◆ 安装方便, 不锈钢主轴连接部分及安装支架均符合NAMUR标准

MODEL APL-2N

- ◆ Enclosure: Weatherproof IP67/NEMA4&4X(Standard) IP68 (Option)
- ◆ Solid and compact design
- ◆ Bolts on visual position indicator (Re-adjustment available upon required direction)
- ◆ Dual cable entries: 2 x1/2 NPT(Standard) M20, PG13.5, PF1/2", PT1/2".(Option)
- ◆ Terminal Strips: 8 points(0.08-25mm²)
- ◆ Captive cover bolts
- ◆ Easy mounting
- ◆ NAMUR standard stainless steel shaft and bracket

APL-3N 系列



- ◆ 防护等级: IP67/NEMA 4& 4X (标准) IP68 (选项)
- ◆ 坚固漂亮的外壳设计
- ◆ 附加限位开关: 3~4个机械开关
- ◆ 附加接线端子 8~16点
- ◆ 开关位置可由指示器清楚辨识
- ◆ 双线接口: 双1/2NPT管接口 (标准) M 20, PG 13.5, PF1/2" PT1/2" (选项)
- ◆ 接线端子: 8点 0.08-2.5mm²
- ◆ 防脱螺栓, 安装方便, 不锈钢主轴连接部分及安装支架均符合NAMUR标准

MODEL APL-3N

- ◆ Enclosure: Weatherproof IP67/NEMA4&4X(Standard) IP68 (Option)
- ◆ Solid and beautiful design & various options available
- ◆ 3-4 additional switches
- ◆ 8-16 points Terminal Strips
- ◆ Bolts on visual position indicator
- ◆ Dual cable entries: 2 x1/2 NPT(Standard) M20, PG13.5, PF1/2", PT1/2".(Option)
- ◆ Terminal Strips: 8 points(0.08-25mm²)
- ◆ Captive cover bolts
- ◆ Easy mounting
- ◆ NAMUR standard stainless steel shaft and bracket

APL-4N 系列



- ◆ 防护等级: IP67/NEMA 4,4X,7,9 (标准) IP68 (选项)
- ◆ 防爆等级 Ex d IIB T6, 通过中国NEPS认证
- ◆ 外壳坚固漂亮
- ◆ 附加限位开关: 3~4个机械开关
- ◆ 附加接线端子 8~20点
- ◆ 多种可选开关
- ◆ 开关位置可由指示器清楚辨识
- ◆ 电缆接入: 2x3/4 NPT (标准) M 20, M 25, PF3/4" PT3/4" 4Cable entries (选项)
- ◆ 导线端口: 8点 0.08-2.5mm²
- ◆ 安装方便, 不锈钢主轴连接部分及安装支架均符合NAMUR标准

MODEL APL-4N

- ◆ Enclosure: Weatherproof IP67/NEMA4,4X,7,9 (Standard) IP68(Option)
- ◆ ExplosionProof: EEX d IIB T6
- ◆ Solid and beautiful design & various options available
- ◆ 3-4 additional switches
- ◆ 8-20 points Terminal Strips
- ◆ various options switches
- ◆ Bolts on visual position indicator
- ◆ Cable entries: 2x3/4 NPT(Standard) M20, M25, PF3/4", PT3/4" 4Cable entries(Option)
- ◆ Terminal Strips: 8 points(0.08-2.5mm²)
- ◆ Captive cover bolts
- ◆ Easy mounting
- ◆ NAMUR standard stainless steel shaft and bracket

APL-5N 系列



- ◆ 防护等级: IP67/NEMA 4,4X,7,9 (标准) IP68 (选项)
- ◆ 防爆等级 Ex d IIB T6, Ex d IIC T6,
- ◆ 外壳坚固漂亮, 外壳上装有主轴(双轴)
- ◆ 容易安装可视位置指示器
- ◆ 独特的设计方案以螺栓形式安装上盖,并以此间定指示器
- ◆ 双缆进入: 2x3/4 PF (标准) M 20, M 25, NPT3/4" PT3/4" (选项)
- ◆ 接线端子: 8点 0.08-2.5mm²
- ◆ 防脱螺栓, 弹簧加固
- ◆ 独特的设计把螺栓固定在外壳内, 打开外壳时螺栓不会掉落
- ◆ 容易安装支架
- ◆ NAMUR标准是不锈钢主轴和不锈钢或钢支架

MODEL APL-5N

- ◆ Enclosure: Weatherproof IP67/NEMA4, 4X, 7, 9 (Standard) IP68(Option)
- ◆ Explosionproof: EEX d IIC T6, EEX ia IIC T6, EEX d IIB T6
- ◆ Solid and compact design
- ◆ Shaft holder built in the cove(Dual shaft)
- ◆ Easy to set the visual position indicator.
- ◆ Unique design to put the visual indicator on the threaded joint type cover.
- ◆ Bolts on visual position indicator
- ◆ Dual Cable entries: 2 x3/4 PF(Standard) M20, M25, NPT3/4", PT3/4"(Option)
- ◆ Terminal Strips: 8 points(0.08-2.5mm²)
- ◆ Captive cover bolts & Spring loaded cover bolts
- ◆ Easy mounting
- ◆ NAMUR standard stainless steel shaft and bracket.
- ◆ Stainless steel(316)housing as option.